

## VT 6100

**Versatile farm trailer with grain, rock, gravel and silage side options.**

### STANDARD FEATURES

- ▶ **CARRYING CAPACITY:** 20T
- ▶ **FLAT BODY:** 6100x2700mm with 4mm Hardox Floor
- ▶ **DIRT SIDES:** 750mm Hardox Sides with up and over hydraulic door
- ▶ **GRAIN SIDES:** 3mm mild steel, 1500mm high with hydraulic door
- ▶ **SILAGE SIDES:** 3mm mild steel, 2250mm high with hydraulic door
- ▶ **AXLES:** 125mmØ 10 stud, 420x180 brakes
- ▶ **SUSPENSION:** Mechanical suspension with 100mm wide 3 leaf springs
- ▶ **DRAWBAR:** sprung, 40mm swivel tow eye
- ▶ **TYRES:** BKT FL693M 560/60Rx22.5 flotation
- ▶ **BRAKES:** Hydraulic
- ▶ **LIGHTS:** LED light system, rear beacon



ROCK/GRAVEL



GRAIN SIDES



SILAGE SIDES



BALE EXTENSION

**No more wasting time and money on dedicated trailers for each material. The Stewart VT 6100 transforms in seconds to handle grain transport, aggregate materials, silage, and more.**

At 6.1m body standard, the Stewart VT 6100 is the most versatile farm trailer on the market, with 4 different side configurations so you can haul exactly what you need.

4 different configurations allows you to quickly switch between grain, rock, gravel, and silage sides to suit our customers' changing demands.

MODEL	CARRYING CAPACITY	BODY LENGTH	BODY WIDTH	TRAY	HYDRAULIC TIPPING	AXLES, BRAKE SIZE	SUSPENSION	TYRES
VT5500	16T	5.5m	2.7m	HARDOX	Twin tip rams	125mmØ 10 stud 300mm x 130mm Hydraulic	Springs	22.5-in. Flotation tyres
VT6100	20T	6.1m	2.7m	HARDOX	Twin tip rams	300mm x 130mm Hydraulic	Draw	22.5-in. Flotation tyres



[www.armorgroup.com.au](http://www.armorgroup.com.au)



**ARMOUR GROUP**

Importers & distributors of premium agricultural equipment