

# Flat Trailers / Bale Handlers



Stewart flat trailers can be supplied with a 4mm steel floor or a 28mm keruing floor for the same price.

The standard Flat Trailer is used with our Livestock Floats, for carrying a float

Bale trailers from 26ft to 36ft based on our standard flat trailer range.

Model	Length	Carrying Capacity	Maximum Speed	Body	Floor Be-arrers	Floor	Braking	Tyres
GX 8 FT	20ft to 22ft	8,000kg	40 km/hr	Standard width 2500mm (8'2"	60x40 RHS	4mm steel Full Length Rope Rai	Hydraulic braking system	12.5/80 x15.3
GX 10 FT	20ft to 26ft	10,000kg	40 km/hr	Standard width 2500mm (8'2"	80x40 RH	4mm steel Full Length Rope Rai	Hydraulic braking system	19S80R 105 Mud Flaps
GX 12FT	26ft to 28ft	12,000kg	40 km/hr	Standard width 2500mm (8'2"	100x50 channel	4mm steel Full Length Rope Rai	Hydraulic braking system	Remould 385/65R x22.5 Mud Flaps
GX 15FT	26ft to 36ft	15,000kg	40 km/hr	Standard width 2500mm (8'2"	100x50 channel	4mm steel Full Length Rope Rai	Hydraulic braking system	Remould 385/65R x22.5 Mud Flaps

## Low Loader Trailers



Our Range is from 8T-22T+ in the Flat and Low Loader Range

Every trailer is custom built, there are a wide variety of optional extra items available to choose from. We can supply open tread ramps, timber clad ramps or steel ramps, the steel ramps can be galvanised or paint finished.

### Optional Extras

- ▶ Fast tow trailer fitted with air braking, ABS and load sensing valve
- ▶ Hydraulic load sensing valve
- ▶ Hydraulic ramps
- ▶ Spray flaps front of wheels
- ▶ Spray flaps front of trailer
- ▶ Galvanised steel toolbox with lockable Stainless Steel lid
- ▶ Lockable plastic toolbox
- ▶ Steel chain storage box in floor
- ▶ Work (reversing) lights
- ▶ Hydraulically operated beaver tail
- ▶ Hydraulically operated floor plate in beaver tail
- ▶ Removeable rear wedge
- ▶ Galvanised outriggers

Model	Length	Capacity
GX 22 LL	7900mm	22,000kg
GX 15 LL	7900mm	15,000kg
GX 10 LL	6100mm	10,000kg